

# Punto LX/ST

Promotional ice cream display cabinet with static refrigeration. Closure on the operator side via methacrylate tilt flap. The cabinet can contain a double level of trays H120 in the display basin.



**REFRIGERANT**  
R404A / R290



**LIGHTING**  
Led



**INSTALLATION**  
Plug-in



**TEMPERATURE (°C)**  
-16/-14



**DEFROST**  
Automatic



**CLIMATIC CLASS**  
7



LX

## STANDARD EQUIPMENT

Swivel casters with brakes

Electronic command panel

LED lighting

Static refrigeration reserve cell  
(only models 6R, 7R, 9R, 12R)

Internal and external pre-painted metal sheet  
basin

Plastic coated metal sheet serving surface

## OPTIONAL

Stainless steel tray 5 litres - 360 x 165 x 120H

Stainless steel tray 4.75 litres - 260 x 165 x 170H

4.75 litre tray spacer kit

White complete cone holder

Stainless steel scoop washer tray

Front adhesive PM\_AD1

## FRONT ADHESIVE PM\_AD1



MODEL			4	6R	7R	9R	12R
			<b>LX-ST</b>	<b>LX-ST</b>	<b>LX-ST</b>	<b>LX</b>	<b>LX</b>
			RS	RS	RS	RS	RS
External dimensions	L x P x H	mm	824 x 760 x 1176	1184 x 800 x 1176	1354 x 800 x 1176	1659 x 800 x 1176	2119 x 800 x 1176
Refrigerant			R290	R404A	R290	R404A	R404A
Refrigeration			Static	Static	Static	Static	Static
Capacity	Gross - Net	lt	-	-	-	-	-
Product temperature		°C	-16 / -14	-16 / -14	-16 / -14	-16 / -14	-16 / -14
Defrost			Electric	Electric	Electric	Electric	Electric
Climatic class		No.	7	7	7	7	7
Environmental conditions		°C/%RH	35 / 75	35 / 75	35 / 75	35 / 75	35 / 75
Compressor	Type - No.		Hermetic - 1	Hermetic - 1	Hermetic - 1	Hermetic - 1	Hermetic - 2
Power supply		V/ph/Hz	230 / 1 / 50	230 / 1 / 50	230 / 1 / 50	230 / 1 / 50	230 / 1 / 50
Electrical input	Standard	W/A	300 / 2.4	590 / 4.1	460 / 2.4	930 / 5.5	1045 / 5.6
	Defrost	W/A	810 / 3.8	810 / 3.8	820 / 3.4	1330 / 5.8	1755 / 8.2
Net weight		kg	69	97	102	160	217